RIGHT-OF-WAY SURVEY FOR FOUND MON SPIKE FOUND MON SPIKE FOUND SPINDLE AT AT SECTION CORNER **KINDER** # MORGAN AT 1/4 CORNER 1/16 CORNER SEC 33 ♥ SEC 34 N 89°46'20" W 1315.97' N 89°46'42" W 1318.13' SEC 4 SEC 3 MILES PROPOERTY DESCRIPTION OF CORRIDOR #1 DESCRIPTION OF CORRIDOR #3 SECTION 4 A 50 feet wide pipeline right-of-way corridor over portions of Section 4, Township 2 South, Range 3 West, Uintah Special Base A 50 feet wide pipeline right-of-way corridor over portions of Section 4, Township 2 South, Range 3 West, Uintah Special Base TOWNSHIP 2 SOUTH, RANGE 3 WEST and Meridian, the widths being 25 feet on each side of the and Meridian, the widths being 25 feet on each side of the following described centerline; following described centerline; UINTAH SPECIAL BASE & MERIDIAN Commencing at the Southeast Corner of the SE1/4 of the NE1/4 Commencing at the Southeast Corner of the SE1/4 of the NE1/4 of said Section 4; of said Section 4; DUCHESNE COUNTY, UTAH Thence North 00°32'55" East 25.00 feet along the East line of Thence North 80°01'29" West 2695.11 feet to the TRUE POINT OF said aliquot part to the TRUE POINT OF BEGINNING; BEGINNING which is on the West line of the SW1/4 of said NE1/4; Thence North 86'04'24" West 453.78 feet; Thence North 88'16'07" East 389.40 feet; Thence North 53'12'23" West 391.60 feet; Thence South 77.51'03" East 774.71 feet; Thence North 17'10'36" West 62.48 feet to the POINT OF Thence South 48'39'38" East 232.57 feet; Thence South 05'55'05" West 157.87 feet to the POINT OF TERMINUS. Said described right-of-way being 907.86 feet in length, with the sidelines being shortened or elongated to intersect TERMINUS which is on the South line of said SW1/4 of said existing pipeline right-of-way lines. aliquot part. Said described right-of-way being 1554.55 feet in length, with the sidelines being shortened or elongated to intersect said aliquot part lines. DESCRIPTION OF CORRIDOR #3 NORTH DESCRIPTION OF CORRIDOR #2 A 50 feet wide pipeline right-of-way corridor over portions of A 50 feet wide pipeline right-of-way corridor over portions of Section 4, Township 2 South, Range 3 West, Uintah Special Base Section 4, Township 2 South, Range 3 West, Uintah Special Base and Meridian, the widths being 25 feet on each side of the and Meridian, the widths being 25 feet on each side of the following described centerline: SCALE: 1"=200' following described centerline; Commencing at the Southeast Corner of the SE1/4 of the NE1/4 Commencing at the Southeast Corner of the SE1/4 of the NE1/4 of said Section 4; of said Section 4; 200 Thence North 68'34'52" West 826.81 feet to the TRUE POINT OF Thence North 00°32'55" East 25.00 feet along the East line of said aliquot part to the TRUE POINT OF BEGINNING; Thence South 79'30'16" West 607.16 feet to the POINT OF Thence North 89°47'25" West 49.92 feet; TERMINUS. Said described right-of-way being 607.16 feet in Thence North 00'31'49" East 419.57 feet; length, with the sidelines being shortened or elongated to intersect Thence North 85'29'50" West 369.39 feet; LINE TABLE existing pipeline rights-of-way. Thence South 54'51'06" West 113.86 feet; BEARING Thence South 64°03'51" West 113.80 feet; Thence South 82'14'02" West 222.68 feet to the POINT OF N 88'16'07" E 389.40 TERMINUS. Said described right-of-way being 1289.22 feet in S 77°51'03" E 774.71 length, with the sidelines intersecting said aliquot part line and S 48'39'38" E 232.57 ending perpendicular to described centerline at said Terminus. S 05'55'05" W S 79'30'16" W 607.16 N 86°04'24" W 453.78 N 53'12'23" W 391.60 FOUND PIPE CORNER POST AT 1/16 N 17'10'36" W CORNER AS PER PEATROSS PLAT S 89°40'10" W 2642.37' (TIE) 62.48 N 89'47'25" W 49.92 904.67' (TIE) POSITION OF 1/16 N 00'31'49" E 419.57 CORNER DETERMINED DESCRIPTION OF 40' WIDE ACCESS RIGHT-OF-WAY N 85'29'50" W 369.39 ON PREVIOUS SURVEY S 54'51'06" W 113.86 A 40 feet wide access right-of-way over portions of S 64.03'51" W 113.80 Section 4, Township 2 South, Range 3 West, Uintah Special Base and Meridian, the widths being 20 feet on each side L14 S 82'14'02" W 222.68' of the following described centerline; JON E. / ELIZABETH M. MILES Commencing at the Northeast Corner of the SE/14 of the PROPERTYNE1/4 of said Section 4; SN:1876 Thence South 89'40'10" West 904.67 feet; Thence South 00'00'00" East 831.41 feet to the TRUE PN:00-0006-2061 POINT OF BEGINNING which is on the centerline of an existing road right-of-way; Thence South 16°10'22" East 176.27 feet to the North line of an existing pipeline right-of-way. Said described EXSTG. ACCESS ROAD right-of-way being 176.27 feet in length, with the sidelines BASIS OF BEARINGS being shortened or elongated to intersect existing THIS SURVEY WAS PERFORMED USING GLOBAL POSITIONING SYSTEM PROCEDURES AND EQUIPMENT right-of-way lines. THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (1/4 CORNER) LOCATED AT LAT. 40°23'18.20359"N AND LONG. 110'10'15.86470"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND SW1/4 SE1/4NE1/4NE1/4OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER EXISTING CATHODIC RIGHT-OF-WAY _ 4+69.49 CL#4 8+38.88 CL#4 9+07.85 CL#3 SURVEYOR'S CERTIFICATE RESIDUE PIPELINE RESIDUE PIPELINE I. D. RYAN ALLRED, DUCHESNE COUNTY, UTAH, DO HEREBY CERTIFY THAT I AM A PROFESSIONAL 40' WIDE LAND SURVEYOR AND THAT I HOLD CERTIFICATE NUMBER 376084 AS PRESCRIBED BY THE STATE ACCESS 50' WIDE R/W RIGHT-OF-WAY OF UTAH. I FURTHER CERTIFY THAT THIS PLAT WAS PREPARED FROM THE FIELD NOTES AND 8+92.02 CL#3 8+92.02 CL#0 /12+38.47 CL#4 CORRIDOR (TYP.) ELECTRONIC DATA COLLECTOR FILES OF AN ACTUAL SURVEY MADE BY ME OR UNDER MY 13+52.20 CL#1 12+89.22 CL#4 PERSONAL SUPERVISION AND THAT THIS PLAT ACCURATELY REPRESENTS SAID SURVEY TO THE 6+07.16 CL#2 BEST OF MY KNOWLEDGE AND BELIEF. T.P.O.B. BEARS N 80°01'29" W 10+66.54 CL#4 2695.11' FROM THE SE COR. OF THE SW1/4 OF THE NE1/4 OF 8+45.37 CL#3 11+64.11 CL#1 50' WIDE R/W 0+00.00 CL#2 CORRIDOR (TYP.) 8+57.23 CL#3 0+00.00 CL#3 T.P.O.B. BEARS N 00°32'55" E T.P.O.B. BEARS N 68°34'38" W 0+00.00 CL#4 25.00' FROM THE SE COR. OF THE SW1/4 OF THE NE1/4 OF 826.68' FROM THE SE COR. OF COMBINE INTO SAME 13+96.68 CL#1 THE SW1/4 OF THE NE1/4 OF SECTION 4 SECTION 4 D. Ryan Allred, Professional Land Surveyor, Certificate No. 376084. (Utah) FOUND 5/8" REBAR WITH N 89'47'25" W 2667.85' (TIE) FOUND MON SPIKE ALUMINUM CAP AT 0+49.92 CL#4 JERRY D. ALLRED & ASSOCIATES, INC. AT 1/4 CORNER POSITION OF CORNER DETERMINED TO BE AT FENCE INTERSECTION SURVEYING CONSULTANTS 1235 NORTH 700 EAST--P.O. BOX 975 DUCHESNE, UTAH 84021 REV 5 NOV 2019 19 AUG 2019 12-121-542 (435) 738-5352